International Journal of Mathematical Archive-4(2), 2013, 184-197

CHEMICAL REACTION EFFECTS ON MHD FREE CONVECTIVE OSCILLATORY FLOW PAST A POROUS PLATE EMBEDDED IN A POROUS MEDIUM IN THE PRESENCE OF HEAT SOURCE

K. Sreelatha^{1*}, B. Rami Reddy² and J. Girish Kumar³

¹Dept. of Science and Humanities, Satya Institute of Tech and Management, Gajularega, Vizianagaram, A.P., India

²Dept of Mathematics, Hindu College, Guntur, A.P., India

³Dept. of Mathematics, Govt. Degree College, Jammalamadugu, Kadapa (Dt.), A.P., India

(Received on: 20-12-12; Revised & Accepted on: 28-01-13)

ABSTRACT

An attempt has been made to study the two-dimensional MHD free convective oscillatory flow of an electrically conducting incompressible viscous fluid past an infinite vertical porous plate embedded in a porous medium, through which suction occurs with constant velocity and chemical reaction in the presence of a heat source. A uniform magnetic field is assumed to be applied transversely to the direction of the free stream taking into account of induced magnetic field. The governing equations involved in the present analysis are solved by using the perturbation method. The velocity, temperature and concentration fields are studied for different parameters such as Grashof number (Gr), modified Grashof number (Gc), Magnetic field parameter (M), Permeability parameter (k), Schmidt number (Sc), Prandtl number (Pr), heat source parameter (Q) and Chemical reaction parameter (Kr), Eckert number (Ec) etc.

Key words: MHD, Chemical reaction, Heat Source, Porous medium etc.

INTRODUCTION:

The influence of magnetic field on viscous incompressible flow of an electrically conducting fluid has its importance in many applications such as extrusion of plastics in the manufacture of rayon and nylon, purification of crude oil, pulp, paper industry, textile industry and in different geophysical cases etc. In many process industries, the cooling of threads or sheets of some polymer materials is of importance in the production line. The rate of cooling can be controlled effectively to achieve final products of desired characteristics by drawing threads, etc. in the presence of an electrically conducting fluid subject to a magnetic field.

MHD plays an important role in agriculture, petroleum industries, geophysics and in astrophysics. Important applications are in the study of geological formations, in exploration and thermal recovery of oil, and in the assessment of aquifers, geothermal reservoirs and underground nuclear waste storage sites. MHD flow has application in metrology, solar physics and in motion of earth's core. Also it has applications in the field of stellar and planetary magnetospheres, aeronautics, chemical engineering and electronics. In the field of power generation, MHD is receiving considerable attention due to the possibilities it offers for much higher thermal efficiencies in power plants.

Jonah Philliph et al. (16) studied the effects of thermal radiation and MHD on the unsteady free convection and mass transform flow past an exponentially accelerated vertical plate with variable temperature. Gireesh Kumar et al. (12) discussed the effects of chemical reaction on transient MHD convection flow past a vertical surface embedded in a porous medium with oscillating temperature. Hemanth Poonia and Chaudhary (14) analyzed the MHD free convection and mass transfer flow over an infinite vertical porous plate with viscous dissipation. Girish Kumar et al. (13) examined the mass transfer effects on MHD flows exponentially accelerated vertical plate in the presence of chemical reaction through porous media.

The study of convective fluid flow with mass transfer along a vertical porous plate in the presence of magnetic field and internal heat generation receiving considerable attention due to its useful applications in different branches of science and technology such as cosmical and geophysical science, fire engineering, combustion modeling etc. Vajravelu (24) studied natural convection flow along a heated semi-infinite vertical plate with internal heat generation.

Cookey et al. (8) analyzed influence of viscous dissipation and radiation on unsteady MHD free convective flow past an infinite heated vertical plate in a porous medium with time dependent suction. Chamkha (6) discussed unsteady MHD convective heat and mass transfer past a semi-infinite vertical permeable moving plate with heat generation. Ahmed (2) looked the effects of unsteady free convective MHD flow through a porous medium bounded by an infinite vertical porous plate. Sharma and Singh (21) discussed the unsteady MHD free convective flow and heat transfer along a vertical porous plate with variable suction and internal heat generation. Sharma et al. (20) analyzed the heat and mass transfer effects on unsteady MHD free convective flow along a vertical porous plate with internal heat generation and variable suction. Soundalgekar (22) investigated the unsteady free convection flow along vertical porous plate with different boundary conditions and viscous dissipation effect.

Convection in porous medium has important applications in many areas including thermal energy storage, flow through filtering devices, utilization of geothermal energy, oil extraction, high performance insulation for buildings, paper industry etc. Hence combined study may give some vital information which will surely be helpful in developing other relevant areas. Kishore et al. (17) analyzed the effects of thermal radiation and viscous dissipation on MHD heat and mass diffusion flow past an oscillating vertical plate embedded in a porous medium with variable surface conditions. Israel – Cookey et al. (15) studied the influence of viscous dissipation and radiation on unsteady MHD free convection flow past an infinite heated vertical plate in a porous medium with time dependent suction.

Chaudhary and Arpita Jain (7) discussed the MHD heat and mass diffusion flow by natural convection past a surface embedded in a porous medium. Seethamahalakshmi *et al.* (19) examined the effects of the chemical reaction and radiation absorption on an unsteady MHD convective heat and mass transfer flow fast a semi-infinite vertical moving in a porous medium with heat source and suction. Abdel-Nasser Osman et al. (1) investigated the analytical solution of thermal radiation and chemical reaction effects on unsteady MHD convection through porous medium with heat source/sink. Chamkha and Khaled (5) looked the effects of hydromagnetic combined heat and mass transfer by natural convection from a permeable surface embedded in fluid saturated porous medium.

Mass diffusion rates can changed tremendously with chemical reactions. In majority cases, a chemical reaction depends on the concentration the concentration of the species itself. A reaction is said to be first order, if the rate of reaction is directly proportional to the concentration itself (Cussler (9)). A few representative areas of interest in which heat and mass transfer combined along with chemical reaction play an important role in chemical industries like in food processing and polymer production.

Chambre and Young (4) have analyzed a first order chemical reaction in the neighborhood of a horizontal plate. Das et al. (10, 11) have studied the effect of homogeneous first order chemical reaction on the flow past an impulsively started vertical plate with uniform heat flux and mass transfer. Again, they are also discussed the mass transfer effects on moving isothermal infinite vertical plate in the presence of chemical reaction. The dimensionless governing equations were solved by the usual Laplace Transform technique. Sudheer Babu et al. (23) have examined the radiation and chemical reaction effects on an unsteady MHD convection flow past a vertical moving porous plate embedded in a porous medium with viscous dissipation. Muthucumaraswamy and Kulaivel (18) looked the chemical reaction effects on moving infinite vertical plate with uniform heat flux and variable mass diffusion

The main objective of the present analysis is to study the unsteady two-dimensional MHD free convective oscillatory flow of an electrically conducting incompressible viscous fluid past an infinite vertical porous plate embedded in a porous medium, in which suction occurs with constant velocity and chemical reaction in the presence of a heat source. The equations of continuity, momentum, energy and diffusion which govern the flow field are solved to the best possible solution.

Nomenclature

С	-	dimensionless concentration, [-]
C	-	concentration, $[molm^{-3}]$
C'_w	-	species concentration at the plate, $[molm^{-3}]$
$\mathcal{C}_{\infty}^{\prime}$	-	species concentration far away from the plate, $[molm^{-3}]$
C_p	-	specific heat at constant pressure, [Jkg ⁻¹ K ⁻¹]
Ď	-	chemical diffusivity, [m ² s ⁻¹]
Ec	-	Eckert number, [-]
$g_{x'}$	-	acceleration due to gravity, [ms ⁻²]
Gc	-	modified Grashof number, [-]
Gr	-	Grashof number, [-]
B_0	-	applied magnetic field, [-]
k'	-	permeability parameter, [-]
κ	-	thermal conductivity, $[Wm^{-1}K^{-1}]$
Pr	-	Prandtl number, [-]

© 2013, IJMA. All Rights Reserved

$p^{'}$	-	pressure, [kgm ⁻¹ s ⁻²]
q'	-	heat flux at the plate, [Wm ⁻²]
Q^{\prime}	-	heat source, [-]
Sc	-	Schmidt number, [-]
K_{r}^{\prime}	-	chemical reaction, [-]
T	-	dimensionless fluid temperature, [-]
$T^{'}$	-	fluid temperature, [K]
T_{∞}^{\prime}	-	temperature of the fluid far away from the plate, [K]
t	-	dimensionless time, [-]
ť	-	the time, [s]
U_0	-	mean free stream velocity, $[ms^{-1}]$
u	-	dimensionless velocity of the fluid at the x' - direction, [-]
u [′]	-	velocity of the fluid at the x' - direction, [ms ⁻¹]
v	-	velocity of the fluid at the y' - direction, [-]
v_0	-	suction velocity, [ms ⁻¹]
x	-	co-ordinate axis along the plate, [-]
<i>y</i> ′	-	co-ordinate axis normal to the plate, [-]

Greek symbols

α	-	absorption coefficient, [m ⁻¹]
β	-	coefficient of thermal expansion, [K ⁻¹]
β^*	-	coefficient of concentration expansion, [(molm ⁻³) ⁻¹]
v	-	kinematic viscosity, $[m^2s^{-1}]$
ρ	-	fluid density, [kgm ⁻³]
σ^{*}	-	Stefan – Boltzman constant, [Wm ⁻² K ⁻⁴]
ω	-	dimensionless frequency of vibration of the fluid, [-]
ω΄	-	frequency of vibration of the fluid, [rads ⁻¹]

FORMULATION OF THE PROBLEM:

We consider the unsteady two-dimensional MHD free convective oscillatory flow of an electrically conducting incompressible viscous fluid past an infinite vertical porous plate embedded in a porous medium, through which suction occurs with constant velocity and chemical reaction in the presence of a heat source. The x' - axis is along the plate in the upward direction and the y' - axis is normal to it. A uniform magnetic field is applied in the direction perpendicular to the plate. Reynolds number is much less than unity and the induced magnetic field is negligible in comparison with the applied magnetic field. It is also assumed that all the fluid properties are constant except that of the influence of the density variation with temperature and concentration in the body force term (Boussinesq's approximation). There is a chemical reaction between the diffusing species and the fluid. The foreign mass present in the flow is assumed to be a low level and hence Soret and Dufour effects are negligible. Under these assumptions, the governing equations of the flow field are:

Continuity equation

$$\frac{\partial v'}{\partial z'} = 0$$
(1)

Momentum equation

$$\rho\left(\frac{\partial u'}{\partial t'} + v'\frac{\partial u'}{\partial y'}\right) = -\frac{\partial p'}{\partial x'} - \rho g_{x'} + v\rho \frac{\partial^2 u'}{\partial y'^2} - \left(\sigma B_0^2 + \rho \frac{v'}{k'}\right)(u')$$
(2)

Energy equation

∂y'

$$\frac{\partial T'}{\partial t'} + \nu' \frac{\partial T'}{\partial y'} = \frac{\kappa}{\rho C_p} \frac{\partial^2 T'}{\partial y'^2} + \frac{\nu}{C_p} \left(\frac{\partial u'}{\partial y'}\right)^2 + \frac{Q'}{\rho C_p} (T' - T'_{\infty})$$
(3)

Diffusion equation

$$\frac{\partial C'}{\partial t'} + v' \frac{\partial C'}{\partial y'^2} = D \frac{\partial^2 C'}{\partial y'^2} - K'_r (C' - C'_{\infty})$$
(4)

Where u' and v' are the components of the velocity parallel and perpendicular to the plate, t' - the time, p' - the pressure, ρ - the fluid density, $g_{x'}$ - the acceleration due to gravity, B_0 - the applied magnetic field, k' - the permeability parameter, T' - the fluid temperature, v - the kinematic viscosity, C_p - the specific heat at constant pressure, κ - the thermal conductivity, Q' - the heat source, C' - the concentration and D- the chemical diffusivity, K'_r - the chemical reaction

The boundary conditions are:

$$u' = 0, v' = -v_0, \frac{\partial T'}{\partial y'} = -\frac{q'}{\kappa}, C' = C'_w at y' = 0$$

$$u' \to U' = U_0 (1 + \varepsilon e^{iw't'}), T' \to T'_{\infty}, C' \to C'_{\infty} as y' \to \infty$$
(5)

Where v_0 is the constant suction velocity and the negative sign indicates that it is towards the plate, q' - the constant heat flux, T'_{∞} - the fluid temperature far away from the plate, C'_w - the species concentration at the plate, C'_{∞} - the species concentration far away from the plate, U_0 - the mean free stream velocity, ω' - the frequency of vibration of the fluid, and ε (ε < 1) - a constant quantity.

For the free stream, equation (2) becomes:

$$\rho \frac{dU'}{dt'} = -\frac{\partial p'}{\partial x'} - \rho_{\infty} g_{x'} - \sigma B_0^2 U' - \rho \frac{v'}{k'} U'$$
(6)

On eliminating
$$\frac{\partial p'}{\partial x'}$$
 between (2) and (6) we get:

$$\rho\left(\frac{\partial u'}{\partial t'} + v'\frac{\partial u'}{\partial y'}\right) = \rho \frac{du'}{dt'} + g_{x'}(\rho_{\infty} - \rho) + v\rho \frac{\partial^2 u'}{\partial y'^2} - \left(\sigma B_0^2 + \rho \frac{v'}{k'}\right) \left(u' - U'(t')\right)$$
(7)

The state equation is

 $g_{x'}(\rho_{\infty} - \rho) = g_{x'}\rho\beta(T' - T_{\infty}') + g_{x'}\rho\beta^{*}(C' - C_{\infty}')$ (8)

Where β is the coefficient of thermal expansion and β^* is the coefficient of concentration expansion

From (7) and (8) we have

$$\frac{\partial u'}{\partial t'} + v' \frac{\partial u'}{\partial y'} = \frac{dU'}{dt'} + g_{x'} \beta(T' - T'_{\infty}) + g_{x'} \beta^* (C' - C'_{\infty}) + v \frac{\partial^2 u'}{\partial y'^2} - \left(\frac{\sigma B_0^2}{\rho} + \frac{v'}{k'}\right) \left(u' - U'(t')\right)$$
(9)

Equation (1) gives:

$$v' = -v_0(v_0 > 0)$$
 (10)

On substituting equation (10), in equations (10), (3) and (4) we take:

$$\frac{\partial u'}{\partial t'} - v_0 \frac{\partial u'}{\partial y'} = \frac{dU'}{dt'} + g_{x'} \beta(T' - T'_{\infty}) + g_{x'} \beta^* (C' - C'_{\infty}) + v \frac{\partial^2 u'}{\partial y'^2} - \left(\frac{\sigma B_0^2}{\rho} + \frac{v'}{k'}\right) (u' - U'(t'))$$
(11)

$$\frac{\partial T'}{\partial t'} - v_0 \frac{\partial T}{\partial y'} = \frac{\kappa}{\rho C_p} \frac{\partial^2 T'}{\partial y'^2} + \frac{v}{C_p} \left(\frac{\partial u'}{\partial y'}\right)^2 + \frac{Q'}{\rho C_p} (T' - T'_{\infty})$$
(12)

$$\frac{\partial c'}{\partial t'} - v_0 \frac{\partial c'}{\partial y'} = D \frac{\partial^2 c'}{\partial y'^2} - K'_r (c' - c'_{\infty})$$
(13)

Using the transformations:

$$y = \frac{y' v_0}{v}, t = \frac{t' v_0^2}{4v}, u = \frac{u'}{U_0}, U = \frac{U'}{U_0}, \omega = \frac{4v\omega'}{v_0^2}T = \frac{T' - T'_{\infty}}{\frac{vq'}{kv_0}}$$

$$C = \frac{C' - C'_{\infty}}{C'_w - C'_{\infty}}, Gr = \frac{g_{x'}\beta v^2 q'}{kU_0 v_0^3}, Gc = \frac{vg_{x'}\beta^*(C'_w - C'_{\infty})}{U_0 v_0^2}, \Pr = \frac{\rho v C_p}{k},$$

$$Ec = \frac{kU_0^2 v_0}{C_p vq'}, M = \frac{\sigma B_0^2 v}{\rho v_0^2}, Q = \frac{v^2 q'}{\kappa v_0^2}, Kr = \frac{K'_r v}{v_0^2}, Sc = \frac{v}{p}, \ k = \frac{k' v^2}{v_0^2}$$
(14)

With the help of the non-dimensional quantities (14), equations (11)-(13) reduce to:

$$\frac{1}{4}\frac{\partial u}{\partial t} - \frac{\partial u}{\partial y} = \frac{1}{4}\frac{dU}{dt} + GrT + GcC + \frac{\partial^2 u}{\partial y^2} - \left(M + \frac{1}{k}\right)(u - U)$$
(15)

$$Pr\left(\frac{1}{4}\frac{\partial T}{\partial t} - \frac{\partial T}{\partial y}\right) = \frac{\partial^2 T}{\partial y^2} + PrEc\left(\frac{\partial u}{\partial y}\right)^2 + QT$$
(16)

$$Sc\left(\frac{1}{4}\frac{\partial C}{\partial t} - \frac{\partial C}{\partial y}\right) = \frac{\partial^2 C}{\partial y^2} - KrScC$$
(17)

With the boundary conditions:

$$u = 0, \qquad \frac{\partial T}{\partial y} = -1, \qquad C = 1 \qquad at \quad y = 0 \\ u \to U(t) = 1 + \varepsilon e^{i \,\omega t}, T \to 0, C \to 0 \ as \ y \to \infty$$
 (18)

SOLUTION OF THE PROBLEM:

Equations (15) - (17) are coupled, non-linear partial differential equations and these cannot be solved in closed form. However, these equations can be reduced to a set of ordinary differential equations, which can be solved analytically. This can be done by representing the velocity, temperature and concentration of the fluid in the neighbourhood of the plate as:

$$u(y,t) = u_0(y) + \varepsilon e^{i \,\omega \, t} u_1(y) + \dots$$
(19)

$$T(y,t) = T_0(y) + \varepsilon e^{i\omega t} T_1(y) + \cdots$$
(20)

$$C(y,t) = C_0(y) + \varepsilon e^{i\omega t} C_1(y) + \cdots$$
(21)

On substituting equations (19)-(21) in equations (15)-(17) we get the following system of differential equations: $\frac{d^{2}u_{0}}{dy^{2}} + \frac{du_{0}}{dy} - \left(M + \frac{1}{k}\right)u_{0} = -\left[GrT_{0} + GcC_{0} + \left(M + \frac{1}{k}\right)\right]$ (22)

$$\frac{d^2 u_1}{dy^2} + \frac{du_1}{dy} - \left(\frac{i\omega}{4} - M - \frac{1}{k}\right) u_1 = -\left[GrT_1 + GcC_1 + \left(\frac{i\omega}{4} + M + \frac{1}{k}\right)\right]$$
(23)

$$\frac{d^2 T_0}{dy^2} + Pr \frac{dT_0}{dy} + QT_0 = -PrEc \left(\frac{du_0}{dy}\right)^2$$
(24)

$$\frac{d^2T_1}{dy^2} + Pr\frac{dT_1}{dy} - \frac{i\omega}{4}PrT_1 + QT_1 = -2PrEc\left(\frac{du_0}{dy}\right)\left(\frac{du_1}{dy}\right)$$
(25)

$$\frac{d^2 C_0}{dy^2} + Sc \frac{dC_0}{dy} - KrScC_0 = 0$$
(26)

$$\frac{d^2 C_1}{dy^2} + Sc \frac{dC_1}{dy} - Sc \left[\frac{i\omega}{4} - Kr\right] C_1 = 0$$

$$\tag{27}$$

The corresponding boundary conditions (18) are:

$$u_{0} = 0, u_{1} = 0, \frac{dT_{0}}{dy} = -1, \frac{dT_{1}}{dy} = 0, C_{0} = 1, C_{1} = 0 \text{ at } y = 0$$

$$u_{0} \to 1, u_{1} \to 1, T_{0} \to 0, T_{1} \to 0, C_{0} \to 0, C_{1} \to 0 \text{ as } y \to \infty$$
(28)

In order to solve the system of the differential equations (22)-(27) we put:

$$u_{0}(y) = u_{01}(y) + Ecu_{02}(y) T_{0}(y) = T_{01}(y) + EcT_{02}(y)$$
(29)

and

$$u_1(y) = u_{11}(y) + Ecu_{12}(y)$$

 $T_1(y) = T_{11}(y) + EcT_{12}(y)$
(30)

In this system, equating the coefficients of Ec^0 and Ec^1 we get:

$$\frac{d^2 u_{01}}{dy^2} + \frac{d u_{01}}{dy} - \left(M + \frac{1}{k}\right) u_{01} = -\left(GrT_{01} + GcC_{01} + \left(M + \frac{1}{k}\right)\right)$$
(31)

$$\frac{d^2 u_{02}}{dy^2} + \frac{d u_{02}}{dy} - \left(M + \frac{1}{k}\right) u_{02} = -(GrT_{02} + GcC_{02})$$
(32)

$$\frac{d^2 T_{01}}{dy^2} + Pr \frac{dT_{01}}{dy} + QT_{01} = 0$$
(33)

$$\frac{d^2 T_{02}}{dy^2} + Pr \frac{dT_{02}}{dy} + QT_{02} = -2PrEc \left(\frac{du_{01}}{dy}\right)^2$$
(34)

$$\frac{d^2 u_{11}}{dy^2} + \frac{d u_{11}}{dy} - \left(\frac{i\omega}{4} + M + \frac{1}{k}\right) u_{11} = -\left(\frac{i\omega}{4} + GrT_{11} + GcC_{11} + M + \frac{1}{k}\right)$$
(35)

$$\frac{d^2 u_{12}}{dy^2} + \frac{d u_{12}}{dy} - \left(\frac{i\omega}{4} + M + \frac{1}{k}\right) u_{11} = -(GrT_{12} + GcC_{12})$$
(36)

$$\frac{d^2 T_{11}}{dy^2} + Pr \frac{dT_{11}}{dy} - \left(\frac{i\omega}{4}Pr - Q\right)T_{11} = 0$$
(37)

$$\frac{d^2 T_{12}}{dy^2} + Pr \frac{dT_{12}}{dy} - \left(\frac{i\omega}{4}Pr - Q\right)T_{12} = -2PrEc \left(\frac{du_{01}}{dy}\right) \left(\frac{du_{11}}{dy}\right)$$
(38)

© 2013, IJMA. All Rights Reserved
188

© 2013, IJMA. All Rights Reserved

Solving the differential equations (26), (27) and (31) – (38), using boundary conditions (39) we get $u_{10} = \alpha_5 e^{\alpha_2 y} + \alpha_3 e^{\beta_2 y} + \alpha_4 e^{\gamma_2 y} + 1$

$$u_{02} = \alpha_{13}e^{\alpha_2 y} + \alpha_6 e^{\beta_2 y} + \alpha_7 e^{2\alpha_2 y} + \alpha_8 e^{2\beta_2 y} + \alpha_9 e^{2\gamma_2 y} + \alpha_{10} e^{(\alpha_2 + \beta_2) y} + \alpha_{11} e^{(\beta_2 + \gamma_2) y} + \alpha_{12} e^{(\gamma_2 + \alpha_2) y}$$
(41)

$$u_{11} = -e^{\alpha_{15}y} + 1 \tag{42}$$

$$u_{12} = \alpha_{20} e^{\alpha_{15}y} + \alpha_{16} e^{\beta_{11}y} + \alpha_{17} e^{(\alpha_2 + \alpha_{15})y} + \alpha_{18} e^{(\beta_2 + \alpha_{15})y} + \alpha_{19} e^{(\gamma_2 + \alpha_{15})y}$$
(43)

$$T_{01} = \frac{-1}{\beta_2} e^{\beta_2 y}$$
(44)

$$T_{02} = \beta_9 e^{\beta_2 y} + \beta_3 e^{2\alpha_2 y} + \beta_4 e^{2\beta_2 y} + \beta_5 e^{2\gamma_2 y} + \beta_6 e^{(\alpha_2 + \beta_2) y} + \beta_7 e^{(\beta_2 + \gamma_2) y} + \beta_8 e^{(\alpha_2 + \gamma_2) y}$$
(45)

$$T_{11} = 0$$
 (46)

$$T_{12} = \beta_{15} e^{\beta_{11}y} + \beta_{12} e^{(\alpha_2 + \alpha_{15})y} + \beta_{13} e^{(\beta_2 + \alpha_{15})y} + \beta_{14} e^{(\gamma_2 + \alpha_{15})y}$$
(47)

$$C_0 = e^{\gamma_2 y} \tag{48}$$

$$C_1 = 0 \tag{49}$$

With the help of (40) – (47) the equations (29) and (30) becomes $u_0 = (\alpha_5 e^{\alpha_2 y} + \alpha_3 e^{\beta_2 y} + \alpha_4 e^{\gamma_2 y} + 1)$

$$= (\alpha_{5}e^{-\beta_{2}y} + \alpha_{3}e^{-\beta_{2}y} + \alpha_{4}e^{-\beta_{2}y} + \alpha_{7}e^{2\alpha_{2}y} + \alpha_{8}e^{2\beta_{2}y} + \alpha_{9}e^{2\gamma_{2}y} + \alpha_{10}e^{(\alpha_{2}+\beta_{2})y} + \alpha_{11}e^{(\beta_{2}+\gamma_{2})y} + \alpha_{12}e^{(\gamma_{2}+\alpha_{2})y}) (50)$$

$$T_{0} = \left(\frac{-1}{\beta_{2}}e^{\beta_{2}y}\right) + Ec\left(\beta_{9}e^{\beta_{2}y} + \beta_{3}e^{2\alpha_{2}y} + \beta_{4}e^{2\beta_{2}y} + \beta_{5}e^{2\gamma_{2}y} + \beta_{6}e^{(\alpha_{2}+\beta_{2})y} + \beta_{7}e^{(\beta_{2}+\gamma_{2})y} + \beta_{8}e^{(\alpha_{2}+\gamma_{2})y}\right)$$
(51)

$$u_{1} = \left(-e^{\alpha_{15}y} + 1\right) + Ec\left(\alpha_{20}e^{\alpha_{15}y} + \alpha_{16}e^{\beta_{11}y} + \alpha_{17}e^{(\alpha_{2} + \alpha_{15})y} + \alpha_{18}e^{(\beta_{2} + \alpha_{15})y} + \alpha_{19}e^{(\gamma_{2} + \alpha_{15})y}\right)$$
(52)

$$T_{1} = Ec(\beta_{15}e^{\beta_{11}y} + \beta_{12}e^{(\alpha_{2} + \alpha_{15})y} + \beta_{13}e^{(\beta_{2} + \alpha_{15})y} + \beta_{14}e^{(\gamma_{2} + \alpha_{15})y})$$
(53)

Finally from the above equations (48) - (53) and with the help of equations (19), (20) and (21) we obtain the velocity, temperature and concentration fields are as follows:

$$\begin{aligned} u(y) &= u_0 + \varepsilon(\cos(wt) + isin(wt))u_1 \\ &= \left(\left(\alpha_5 e^{\alpha_2 y} + \alpha_3 e^{\beta_2 y} + \alpha_4 e^{\gamma_2 y} + 1 \right) \\ &+ Ec \left(\alpha_{13} e^{\alpha_2 y} + \alpha_6 e^{\beta_2 y} + \alpha_7 e^{2\alpha_2 y} + \alpha_8 e^{2\beta_2 y} + \alpha_9 e^{2\gamma_2 y} + \alpha_{10} e^{(\alpha_2 + \beta_2) y} + \alpha_{11} e^{(\beta_2 + \gamma_2) y} \\ &+ \alpha_{12} e^{(\gamma_2 + \alpha_2) y} \right) + \varepsilon (\cos(wt) + isin(wt)) (-e^{\alpha_{15} y} + 1) \\ &+ Ec \left(\alpha_{20} e^{\alpha_{15} y} + \alpha_{16} e^{\beta_{11} y} + \alpha_{17} e^{(\alpha_2 + \alpha_{15}) y} + \alpha_{18} e^{(\beta_2 + \alpha_{15}) y} + \alpha_{19} e^{(\gamma_2 + \alpha_{15}) y} \right) \end{aligned}$$

$$T(y) = T_{0} + \varepsilon (\cos(wt) + isin(wt))T_{1}$$

$$= \left(\left(\frac{-1}{\beta_{2}} e^{\beta_{2}y} \right) + Ec \left(\beta_{9} e^{\beta_{2}y} + \beta_{3} e^{2\alpha_{2}y} + \beta_{4} e^{2\beta_{2}y} + \beta_{5} e^{2\gamma_{2}y} + \beta_{6} e^{(\alpha_{2} + \beta_{2})y} + \beta_{7} e^{(\beta_{2} + \gamma_{2})y} + \beta_{8} e^{(\alpha_{2} + \gamma_{2})y} \right) \right)$$

$$+ (\cos(wt) + isin(wt)) \left(Ec \left(\beta_{15} e^{\beta_{11}y} + \beta_{12} e^{(\alpha_{2} + \alpha_{15})y} + \beta_{13} e^{(\beta_{2} + \alpha_{15})y} + \beta_{14} e^{(\gamma_{2} + \alpha_{15})y} \right) \right)$$
(55)

$$C(y) = C_0 + \varepsilon(\cos(wt) + isin(wt))C_1 = e^{\gamma_2 y}$$

(56)

(54)

(40)

RESULTS AND DISCUSSIONS:

The chemical reaction effects on MHD free convective oscillatory flow past a porous plate embedded in a porous medium and in the presence of heat source have been studied. The governing equations are solved by using

perturbation method and approximate solutions are obtained for velocity, temperature and concentration fields. The effects of the flow parameters such as Chemical reaction parameter (Kr), Heat source parameter (Q), Prandtl number (Pr), Eckert number (Ec), Schmidt number (Sc), Grashof number for heat and mass transfer (Gr, Gc), magnetic parameter or Hartmann number (M) and permeability parameter (k) on the velocity, temperature and concentration profiles of the flow field are presented with help of velocity, temperature and concentration profile.

Figs. 1(a) and 1(b) illustrate the effect of chemical reaction parameter Kr on velocity and concentration distributions in the boundary layer. It is noticed from the Fig. 1(a) that the velocity at the start of the boundary layer increases slowly till it attains the maximum value, after that they are decreasing and this trend is seen for all the values of the parameter Kr. From Fig. 1(b) it can be observed that increasing the value of the chemical reaction parameter, decreases the concentration of species in the boundary layer, this is due to the fact that destructive chemical reduces the solutal boundary thickness and increases the mass transfer.

Figs. 2(a) and 2(b) depict the velocity (u) and temperature (T) profiles for different values of the heat source parameter Q. It is noticed from the figure 2(a) that when heat is generated the buoyancy force increase, which induces the flow rate to increase giving rise to the increase in the velocity profiles. The effect of Q on temperature profiles are shown in 2(b). It is clear that the heat generation increases, the temperature is also increases.

Figs. 3(a) and 3(b) are shown that the behavior of the velocity (u) and temperature (T) for different values of the Prandtl number Pr. The numerical results show that the effect of increasing values of Pr results in a decreasing velocity. From Fig. 3(b), it is observed that an increase in Pr results in a decrease of the thermal boundary layer thickness and in general lower average temperature within the boundary layer. The reason is that smaller values of Pr are equivalent to increase in the thermal conductivity of the fluid and therefore heat is able to diffuse away from the heated surface more rapidly for higher values of Pr. Hence in the case of smaller Prandtl numbers as the thermal boundary layer is thicker and therefore the rate of heat transfer is reduced.

The influence of the viscous dissipation parameter i.e., the Eckert number (Ec) on velocity and temperature are shown in Fig. 4(a) and 4(b). The velocity and temperature both are increases with increasing Eckert number. It expresses the relationship between the kinetic energy in the flow and the enthalpy. It embodies the conversion of kinetic energy in to internal energy by work done against the viscous fluid stresses. Greater viscous dissipative heat causes a rise in the temperature as well as the velocity.

The effects of Schmidt number on the velocity (u) and concentrations (C) are displays in Figs. 5(a) and 5(b). As the Schmidt number increases, the concentration decreases. This causes the concentration buoyancy effects to decrease yielding a reduction in the fluid velocity. Reductions in the velocity and concentration distributions are accompanied by simultaneous reductions in the velocity and concentration boundary layers.

The velocity profiles for different values of the thermal Grashof number Gr are described in Fig. 6(a). It is observed that an increase in Gr leads to arise in the values of velocity. Hence the positive values of Gr correspond to cooling of the plate. In addition, it is observed that the velocity increases rapidly near wall of the plate as Grashof number increases and then decays to the free stream velocity. For the case of different values of the solutal Grashof number Gc, the velocity profiles in the boundary layer are shown in Fig. 6(b). It is observed that an increase in Gc, leads to a rise in the values of velocity.

The influence of magnetic parameter or Hartmann number M, on the velocity (u) is shown in Fig.7. An increase in M reduces the velocity. The application of a transverse magnetic field to an electrically conducting field gives rise to a resistive type of force called Lorentz force. This force has the tendency to slow down the fluid. This trend is apparent from Fig.7.

Fig. 8 depicts the velocity profiles for different values of permeability parameter k. Clearly as k increases the peak value of velocity across the boundary layer tends to increase rapidly near wall of the porous plate

CONCLUSIONS

We summarize below the following results of physical interest on the velocity, temperature and concentration distribution of the flow field.

- 1. A growing magnetic parameter or Prandtl number or Schmidt number or chemical reaction parameter retards the velocity of the flow field at all points.
- 2. The effect of increasing Grashof number or modified Grashof number or permeability parameter or Eckert number or Heat source is to accelerate velocity of the flow field at all points.

© 2013, IJMA. All Rights Reserved

- 3. A growing Prandtl number decreases temperature of the flow field at all points
- 4. The Eckert number or Heat source increase the leads to increase the temperature at all points.
- 5. The growing Schmidt number or Chemical reaction parameter decreases the concentration of the flow field at all points.

REFERENCES

- 1. Abdel-Nasser A Osman Abo-Dahad S M and Mohamed R A., Analytical solution of thermal radiation and chemical reaction effects on unsteady MHD convection through porous media with heat source/sink, Mathematical Problems in Engineering, Vol.2011, Article ID 205181, pp.1-18, 2011.
- 2. Ahmed S., Effects of unsteady free convective MHD flow through a porous medium bounded by an infinite vertical porous plate, Bull. Cal. Math. Soc., 90, pp.507-522, 2007.
- 3. Basanth Kumar Jha and Ravindra Prasad., Free convection and mass transfer effects on the flow past an accelerated vertical plate with heat source, Mechanics Research Communications, Vol. 17, pp. 143-148, 1990.
- 4. Chambre PL and Young JD., On the diffusion of chemically reactive species in a laminar boundary layer flow, The Physics of fluids, Vol. 1, pp. 48-54, 1958.
- Chamkha A J and Khaled A R., Hydromagnetic combined heat and mass transfer by natural convetion from a permeable surface embedded in fluid saturated porous medium, International Journal of Numerical methods for Heat and Fluid Flow, 10(5), pp.455-476, 2000.
- 6. Chamkha AJ., Unsteady MHD convective heat and mass transfer past a semi-infinite vertical permeable moving plate with heat absorption, Int. J. Sci. Engg., 13 (4), pp. 359-364, 2010.
- 7. Chaudhary R C and Arpita Jain., MHD heat and mass diffusion flow by natural convection past a surface embedded in a porous medium, Theoretical Applied Mechanics, Vol. 36, No.1, pp.1-27, 2009.
- Cookey C. Ogulu A and Omubo-Pepple VB., Influence of viscous dissipation and radiation on unsteady MHD free convective flow past an infinite heated vertical plate in a porous medium with time dependent suction, Int. J. Heat Mass Transfer, 46, pp. 2305-2311, 2003.
- 9. Cussler EL., Diffusion mass transfer in fluid systems, Cambridge University Press, 1988.
- Das UN Deka RK and Soundalgekar VM., Effects on mass transfer on flow past an impulsively started infinite vertical plate with constant heat flux and chemical reaction, Foushing im ingenicurwesen, Vol. 60, pp. 284-287, 1994.
- 11. Das UN Deka RK and Soundalgekar VM., Effects on mass transfer on flow past an impulsively started infinite vertical plate with a chemical reaction, The Bulletin GUMA, Vol. 5, pp.13-20, 1999.
- Gireesh Kumar J Ramakrishna S and Sivaiah M., Effects of chemical reaction on transient MHD convection flow past a vertical surface embedded in a porous medium with oscillating temperature, Ultra Scientist, Vol. 21(3) M, pp. 889-896, 2009.
- 13. Girish Kumar J Kishore PM and Ramakrishna S., Mass transfer effects on MHD flows exponentially accelerated isothermal vertical plate in the presence of chemical reaction through porous media, Advances in Applied Sciences Research, 3(4), pp.2134-2140, 2012.
- 14. Hemanth Poonia and Chaudhry R.C., MHD free convection and mass transfer flow over an infinite vertical porous plate with viscous dissipation, Theoreq. Appl. Mech., Vol. 37(4), pp.263-287, 2010.
- Israel Cookey C Ogulu A and Omubo Pepple VM., The influence of viscous dissipation and radiation on unsteady MHD free convection flow past an infinite heated vertical plate in a porous medium with time dependent suction, Int. J. Heat Mass Transfer, 46, 13, pp.2305-2311, 2003.
- 16. Jonah Philliph K Rajesh V and Vijaya Kumar Varma S., Effects of thermal radiation and MHD on the unsteady free convection and mass transform flow past an exponentially accelerated vertical plate with variable temperature, International Journal of Mathematical Archive, Vol. 3(4), pp. 1392-1404, 2012.
- 17. Kishore PM Rajesh V and Vijayakumar Verma S., The effects of thermal radiation and viscous dissipation on MHD heat and mass diffusion flow past an oscillating vertical plate embedded in a porous medium with variable surface conditions, Theoret. Appl. Mech., Vol.39, No.2, pp.99-125, 2012.
- 18. Muthucumaraswamy, R., and Kulaivel, T., Chemical reaction effects on moving infinite vertical plate with uniform heat flux and variable mass diffusion, Forschung im-Ingenieurwesen, 68, pp.101-104, 2003.
- 19. Seethamahalakshmi Ramana Reddy G V and Prasad B D C N., Effects of the chemical reaction and radiation absorption on an unsteady MHD convective heat and mass transfer flow past a semi-infinite vertical moving in a porous medium with heat source and suction, IOSR Journal of Engineering, Vol.1, Issue 1, pp.028-036, 2011.
- 20. Sharma PR Dadkeech IK and Gurminder Singh., Heat and mass transfer effects on unsteady MHD free convective flow along a vertical porous plate with internal heat generation and variable suction, Int. J. of Math Archive, 3(5), pp. 2163-2172, 2012.
- 21. Sharma PR Singh G., Unsteady MHD free convective flow and heat transfer along a vertical porous plate with variable suction and internal heat generation, Int. J. Appl. Math and Mech., 4, pp. 1-8, 2008.
- 22. Soundalgekar VM., Viscous dissipation effect on unsteady free convective flow past an infinite vertical porous plate with constant suction, Int. J. Heat Mass Transfer, 15, pp.1253-1261, 1971.
- 23. Sudheer Babu M Satya Narayana PV Sankar Reddy T and Umamaheswara Reddy D., Radiation and chemical reaction effects on an unsteady MHD convection flow past a vertical moving porous plate embedded in a porous medium with viscous dissipation, Advances in Applied Science Research, 2(5), pp.226-239, 2011.
- © 2013, IJMA. All Rights Reserved

24. Vajravelu K., Natural convection at a heated, semi-infinite vertical plate with internal heat generation, Acta Mech., 34, pp.153-159, 1979.

APPENDIX

$$\begin{split} a_{1} &= \frac{-1 + \sqrt{1 + 4 \left(M + \frac{1}{k}\right)}}{2}, \ a_{2} &= \frac{-1 - \sqrt{1 + 4 \left(M + \frac{1}{k}\right)}}{2}, \ a_{3} &= \frac{Gr}{\beta_{2} \left(\beta_{2}^{2} + \beta_{2} - \left(M + \frac{1}{k}\right)\right)}, \ a_{4} &= \frac{gc}{r_{2}^{2} + r_{2} - \left(M + \frac{1}{k}\right)}, \\ a_{5} &= -\left[1 + a_{3} + a_{4}\right], \ a_{6} &= \frac{-Gr\beta_{9}}{\beta_{2}^{2} + \beta_{2} - \left(M + \frac{1}{k}\right)}, \ a_{7} &= \frac{-Gr\beta_{3}}{(2a_{2})^{2} + (2a_{2}) - \left(M + \frac{1}{k}\right)}, \\ a_{8} &= \frac{-Gr\beta_{4}}{(2\beta_{2})^{2} + (2\beta_{2}) - \left(M + \frac{1}{k}\right)}, \ a_{9} &= \frac{-Gr\beta_{5}}{(2r_{2})^{2} + (2r_{2}) - \left(M + \frac{1}{k}\right)}, \\ a_{11} &= \frac{-Gr\beta_{6}}{(r_{2} + \beta_{2})^{2} + (2\beta_{2}) - \left(M + \frac{1}{k}\right)}, \ a_{12} &= \frac{-Gr\beta_{6}}{(r_{2} + a_{2})^{2} + (0\gamma_{2} + \beta_{2}) - \left(M + \frac{1}{k}\right)}, \\ a_{13} &= -\left[a_{6} + a_{7} + a_{8} + a_{9} + a_{10} + a_{11} + a_{12}\right], \\ a_{14} &= \frac{-1 + \sqrt{1 + 4 \left(\frac{W + M + 1}{k}\right)}}{2}, \ a_{15} &= \frac{-1 - \sqrt{1 + 4 \left(\frac{W + M + 1}{k}\right)}}{2}, \ a_{16} &= \frac{-Gr\beta_{15}}{\beta_{11}^{2} + \beta_{11} - \left(\frac{W + M + 1}{k}\right)}, \\ a_{17} &= \frac{-Gr\beta_{12}}{(a_{2} + a_{15})^{2} + (a_{2} + a_{15}) - \left(\frac{W + M + 1}{k}\right)}, \ a_{18} &= \frac{-Gr\beta_{13}}{(\beta_{2} + a_{15})^{2} + (\beta_{2} + a_{15}) - \left(\frac{W + M + 1}{k}\right)}, \\ a_{19} &= \frac{-Gr\beta_{14}}{(r_{2} + a_{15})^{2} + (r_{2} + a_{15}) - \left(\frac{W + M + 1}{k}\right)}, \ a_{20} &= -\left[a_{16} + a_{17} + a_{18} + a_{19}\right] \\ \beta_{1} &= \frac{-Pr + \sqrt{Pr^{2} + 4(-Q)}}{2}, \ \beta_{2} &= \frac{-2Pr Ec \left(a_{2}a_{2}a_{2}\right)^{2}}{(2r_{2})^{2} + Pr \left(a_{2} + \beta_{2}\right)^{2}}, \ \beta_{6} &= \frac{-2Pr Ec \left(a_{2}a_{3}b_{2}\right)^{2}}{(2r_{2})^{2} + Pr \left(a_{2} + \beta_{2}\right)^{2}}, \\ \beta_{7} &= \frac{-4Pr Ec \beta_{2}ra_{3}a_{4}}{(2r_{2}\beta_{2}) + Pr \left(\beta_{2} + r_{2}\right) + \beta_{7}}, \ \beta_{8} &= \frac{-4Pr Ec a_{2}r_{2}a_{4}a_{5}}{(2r_{2}\beta_{2})^{2} + Pr \left(a_{2} + r_{2}\right)}, \\ \beta_{14} &= \frac{-2Pr Ec \left(\beta_{2}a_{3}a_{15}}{(2r_{2}\beta_{2})^{2} + Pr \left(a_{2} + r_{2}\right) + \beta_{7}}, \ \beta_{14} &= \frac{-2Pr Ec \left(\beta_{2}a_{3}a_{15}}{(2r_{2}\beta_{2})^{2} + Pr \left(\alpha_{2} + \alpha_{2}\right)}, \\ \beta_{14} &= \frac{-2Pr Ec \left(\beta_{2}a_{3}a_{15}}{(2r_{2}\beta_{2}) + Pr \left(\alpha_{2} + \alpha_{2}\right)}, \ \beta_{14} &= \frac{2Pr Ec \left(\beta_{2}a_{3}a_{15}}{(2r_{2}\beta_{2}) + Pr \left(\alpha_{2} + \alpha_{2}\right)}, \ \beta_{14} &= \frac{2Pr Ec \left(\beta_{2}a_{3}a_{15}}{(2r_{2}\beta_{2}) + Pr \left(\alpha_{2} + \alpha_{2}\right$$

GRAPHS



Figure - 1(a): Velocity profile for different values of chemical reaction parameter 'Kr' when Gr = 5, Gc = 2, Ec = 0.001, Pr = 0.7, Sc = 0.22, M = 1.0, k = 0.1, Q = 0.05.



Figure - 1(b): Concentration profile for different values of chemical reaction parameter 'Kr' when Sc = 0.22



Figure - 2(a): Velocity profile for different values of Heat source parameter 'Q' when Gr = 5, Gc = 2, Ec = 0.001, Pr = 0.7, Sc = 0.22, M = 1.0, k = 0.1, Kr = 0.2.

K. Sreelatha^{1*}, B. Rami Reddy² and J. Girish Kumar³/ CHEMICAL REACTION EFFECTS ON MHD FREE CONVECTIVE OSCILLATORY... / IJMA- 4(2), Feb.-2013.



Figure - 2(b): Temperature profile for different values of Heat source parameter 'Q' when Gr = 5, Gc = 2, Ec = 0.001, Pr = 0.7, Sc = 0.22, M = 1.0, k = 0.1, Kr = 0.2.



Figure - 3(a): Velocity profile for different values of Prandtl number 'Pr' when Gr = 5, Gc = 2, Ec = 0.001, Kr = 0.2, Sc = 0.22, M = 1.0, k = 0.1, Q = 0.05.



Figure - 3(b): Temperature profile for different values of Prandtl number 'Pr' when Gr = 5, Gc = 2, Ec = 0.001, Kr = 0.2, Sc = 0.22, M = 1.0, k = 0.1, Q = 0.05.

K. Sreelatha^{1*}, B. Rami Reddy² and J. Girish Kumar³/ CHEMICAL REACTION EFFECTS ON MHD FREE CONVECTIVE OSCILLATORY... / IJMA- 4(2), Feb.-2013.



Figure - 4(a): Velocity profile for different values of Eckert number 'Ec' when Gr = 5, Gc = 2, Kr = 0.2, Pr = 0.7, Sc = 0.22, M = 1.0, k = 0.1, Q = 0.05.



Figure - 4(b): Temperature profile for different values of Eckert number 'Ec' when Gr = 5, Gc = 2, Kr = 0.2, Pr = 0.7, Sc = 0.22, M = 1.0, k = 0.1, Q = 0.05.



Figure - 5(a): Velocity profile for different values of Schmidt number 'Sc' when Gr = 5, Gc = 2, Ec = 0.001, Pr = 0.7, Kr = 0.2, M = 1.0, k = 0.1, Q = 0.05.



Figure - 5(b): Concentration profile for different values of Schmidt number 'Sc' when Kr = 0.2



Figure - 6(a): Velocity profile for different values of Grashof number 'Gr' when Gc = 2, Kr = 0.2, Ec = 0.001, Pr = 0.7, Sc = 0.22, M = 1.0, k = 0.1, Q = 0.05.



Figure - 6(b): Velocity profile for different values of modified Grashof number 'Gc' when Gr = 5, Kr = 0.2, Ec = 0.001, Pr = 0.7, Sc = 0.22, M = 1.0, k = 0.1, Q = 0.05.



Figure - 7: Velocity profile for different values of magnetic parameter 'M' when Gr = 5, Gc = 2, Kr = 0.2, Ec = 0.001, Pr = 0.7, Sc = 0.22, k = 0.1, Q = 0.05.



Figure - 8: Velocity profile for different values of permeability parameter 'k' when Gr = 5, Gc = 2, Kr = 0.2, Ec = 0.001, Pr = 0.7, Sc = 0.22, M = 1.0, Q = 0.05.

