International Journal of Mathematical Archive-8(8), 2017, 1-14 MAAvailable online through www.ijma.info ISSN 2229 - 5046

VISCOUS DISSIPATION AND PARTIAL SLIP EFFECTS ON MHD BOUNDARY LAYER FLOW OF NANOFLUIDAND HEAT TRANSFER OVER A NONLINEAR STRETCHING SHEET WITH NON-UNIFORM HEAT SOURCE

Y. DHARMENDAR REDDY1*, V. SRINIVASA RAO², L. ANAND BABU³

^{1,2,3}Departtment of Mathematics, Anurag Group of Institutions, Venkatapur, Ghatkesar, Medchal, 500088, Telangana, India.

(Received On: 10-06-17; Revised & Accepted On: 31-07-17)

ABSTRACT

T his paper deals with the steady two-dimensional laminar flow of a viscous nanofluid of magnetohydrodynamic (MHD) flow and heat transfer of the boundary layer flow over a nonlinear stretching sheet. The flow is caused by a nonlinear stretching sheet with effect of velocity slip and variable temperature in the presence of viscous dissipation and non-uniform heat source parameter. The resulting governing equations are converted into a system of nonlinear ordinary differential equations by applying a suitable similarity transformation and then solved numerically using Keller-Box technique. The effect of different flow parameters on velocity, temperature and concentration profiles are presented in both graphical and tabular forms. Numerical values of local skin-friction coefficient, local Nusselt number and Sherwood number are tabulated. It is found that the velocity decreases and the temperature & concentration are increases with increase of velocity slip parameter.

Keywords: Non-uniform heat source, Viscous Dissipation, Nanofluid, MHD, Nonlinear Stretching sheet, Velocity slip.

INTRODUCTION

The boundary layer flow and heat transfer over a stretching sheet have important aspects not only from a theoretical point of view but also concerning their practical applications in the paper production, polymer industry, crystal growing, food processing etc. The boundary layer flow problem over a stretching sheet was first studied by Crane [1], he analyzed an exact solution for the developing problem. Afterwards, the boundary layer flows by linear and nonlinear stretching surfaces have attracted a great deal of attention of the researchers. R. Cortell [2] investigated on fluid flow and radiative nonlinear heat transfer over a stretching sheet. The effect of variable fluid properties on the hydromagnetic flow and heat transfer over a non-linearly stretching sheet was investigated by K.V. Prasad *et al.* [3].

Magnetohydrodynamic (MHD) flow and heat transfer due to the effect of magnetic fields on the boundary layer flow, it acts as electrically conducting fluids. In addition, this type of flow detects many applications in engineering problems such as MHD generators, plasma studies, nuclear reactors and geothermal energy extractions. M. Subhas Abel and Mahantesh M. Nandeppanavar [4] discussed heat transfer in MHD viscoelastic boundary layer flow over a stretching sheet with non-uniform heat source/sink. MHD flow and heat transfer over a stretching surface with variable thermal conductivity and partial slip was analyzed by Mahantesh *et al.* [5]. Asterios Pantokratoras [6] studied numerically the MHD boundary layer flow over a heated stretching sheet with variable viscosity.

In recent years, some studies have been given to the interest of nano fluids of convective transport. Conventional heat transfer fluids, including oil, water and ethylene glycol mixture are inadequate heat transfer fluids, since the thermal conductivity of these fluids plays an important role on the heat transfer coefficient between the heat transfer medium and the heat transfer surface. Therefore, several methods have been taken to improve the thermal conductivity of these fluids by suspending nano/micro or larger-sized particle materials in liquids. An advanced technique to improve heat transfer is by using nanoparticles in the base fluid. Nanotechnology has been widely used in industry, since materials with size of nanometers have unique physical and chemical properties. Nano-scale particle added fluids are called as nanofluid and these nanoparticles range in diameter between 1 - 100 nm. Nanofluid term was coined by Choi firstly [7].

Corresponding Author: Y. Dharmendar Reddy^{1*} ¹Departtment of Mathematics, Anurag Group of Institutions, Venkatapur, Ghatkesar, Medchal, 500088, Telangana, India.

Khan and Pop [8] derived Boundary-layer flow of a nanofluid past a stretching sheet. MHD boundary layer flow and heat transfer of nanofluids over a nonlinear stretching sheet using R.K method by Mabood *et al.* [9]. Malvandi *et al.* [10] analyzed boundary layer flow and heat transfer of nanofluid induced by anon-linearly stretching sheet using homotopy analysis method. Sheikholeslami *et al.* [11] discussed MHD nanofluid flow and heat transfer considering viscous dissipation using numerical technique. Hydromagnetic nanofluid flow due to a stretching or shrinking sheet with viscous dissipation and chemical reaction effects was analyzed numerically by P.K. Kameswaran *et al.* [12]. Dulal Pal and Gopinath Mandal [13] investigated the mixed convection-radiation on stagnation-point flow of nanofluids over a stretching/shrinking sheet in a porous medium with heat generation and viscous dissipation. Rizwan Ul Haq *et al.* [14] discussed the effect of thermal radiation and slip effects on MHD stagnation point flow of nanofluid over a stretching sheet.

Rana and Bhargava [15] examined mixed convection flow of nanofluids with heat source or sink along a vertical plate using numerical technique. Nandy and Mahapatra [16] analyzed the stagnation point flow of nanofluids over a stretching sheet or shrinking sheet with effects of slips and heat generation/absorption. A. Alsaediet. *et al.* [17] discussed the effects of heat generation/absorption on stagnation point flow of nanofluid over a surface with convective boundary conditions. Noghrehabadi *et al.* [18] studied effect of partial slip boundary condition on the flow and heat transfer of nanofluids past stretching sheet with constant wall temperature. Magnetohydrodynamic (MHD) mixed convection slip flow and heat transfer over a vertical porous plate problem was discussed by Swati Mukhopadhyay and Iswar Chandra Mandal [19]. Mustafa *et al.* [20] investigates motion of nanofluid in a channel with wall properties. Bhattacharyya *et al.* [21] explained Slip effects on boundary layer stagnation-point flow and heat transfer towards a stretching/shrinking surface with non-uniform heat source/sink. Dulal Pal and Gopinath Mandal [23] investigated the effect of thermal radiation and MHD on boundary layer flow of micropolar nanofluid past a stretching sheet with non-uniform heat source/sink. Tasawar Hayat *et al.* [24] studied the effect of inclined magnetic field and heat source/sink aspects in flow of nanofluid with nonlinear thermal radiation.

The objective of the present paper is to study the MHD nanofluid flow and heat transfer over a nonlinear stretching sheet with partial slip effects. Therefore to extend the work of Mahantesh *et al.* [25] by considering viscous dissipation in to account. Using the similarity transformations, the set of governing P.D.E. and the boundary conditions are reduced to a system of non-linear ordinary differential equations which are solved numerically using Keller-Box method and the effects of the governing parameters on the flow field are discussed.

FORMULATION OF THE PROBLEM

Consider a two dimensional, incompressible viscous and steady fluid flow of a water-based nanofluid flow past a nonlinear stretching surface. The sheet is extended with velocity $u_w = bx^n$ with fixed origin location, where *n* is a nonlinear stretching parameter, *b* is a constant, and *x* is the coordinate measured along with the stretching surface. The nanofluid flows at $y \ge 0$, where *y* is the coordinate normal to the surface. The fluid is electrical conducting due to an applied magnetic field B(x) normal to the stretching sheet. The magnetic Reynolds number is assumed small and so, the induced magnetic field can be considered negligible. The wall temperature T_w and the nanoparticle fraction C_w are assumed constant at the stretching surface. When *y* tends to infinity, the ambient values of temperature and nano particle fraction are denoted by T_{∞} and C_{∞} , respectively. The boundary layer equations that govern the present flow, as per the above assumptions, are



Fig (i): Physical model and coordination system

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0 \tag{1}$$

$$u\frac{\partial u}{\partial x} + v\frac{\partial u}{\partial y} = v\frac{\partial^2 u}{\partial y^2} - \frac{\sigma B^2(x)}{\rho_f}u$$
(2)

$$u\frac{\partial T}{\partial x} + v\frac{\partial T}{\partial y} = \alpha \frac{\partial^2 T}{\partial y^2} + \frac{v}{c_p} \left(\frac{\partial u}{\partial y}\right)^2 + \tau \left\{ D_B \frac{\partial T}{\partial y} \frac{\partial C}{\partial y} + \frac{D_T}{T_{\infty}} \left(\frac{\partial T}{\partial y}\right)^2 \right\} - \frac{1}{\left(\rho c_p\right)_f} q'''$$
(3)

$$u\frac{\partial C}{\partial x} + v\frac{\partial C}{\partial y} = D_B \frac{\partial^2 C}{\partial y^2} + \frac{D_T}{T_{\infty}} \left(\frac{\partial^2 T}{\partial y^2}\right)$$
(4)

The boundary sheet is stretched nonlinearly with a velocity proportional to x coordinate (i.e., the distance from a slit); hence the appropriate boundary conditions for the problem are

$$u = u_w + A_1 \frac{\partial u}{\partial y}, v = 0, T = Ax^{\lambda}, C = C_w \text{ at } y = 0$$
(5)

$$u = 0, T \to T_{\infty}, C \to C_{\infty}$$
 as $y \to \infty$ (6)
where x and y denote the cartesian coordinates along and normal to the sheet, respectively, u and v are the velocity

components of the fluid in the x and y directions, respectively, ρ is the fluid density, $v = \frac{\mu}{\rho}$ is the kinematic

viscosity, μ is the viscosity, T is the temperature, C is the concentration, k is the thermal conductivity, and c_p is the specific heat at constant pressure.

Where $u_w = bx^n$, A_1 is the velocity slip parameter, $\alpha = \frac{k}{(\rho c)_f}$ is the thermal diffusivity, $\tau = \frac{(\rho c)_p}{(\rho c)_f}$ is the ratio

between the effective heat capacity of the nanoparticle material and the heat capacity of the ordinary fluid. We assume that the variable magnetic field $B(x) = B_0 x^{n-1/2}$, where B_0 is constant. q''' is the non-uniform heat source, which is modeled as:

$$q''' = \left(\frac{ku_w(x)}{x\upsilon}\right) \left[A^* \left(T_w - T_\infty\right) \exp\left(-y\sqrt{\frac{b(n+1)}{2\upsilon}} x^{\frac{n-1}{2}}\right) + B^* \left(T - T_\infty\right) \right]$$
(7)

where A^* and B^* are parameters of the space and temperature dependent internal heat generation/absorption. The case $A^* > 0$ and $B^* > 0$ corresponds to internal heat generation while $A^* < 0$ and $B^* < 0$ corresponds to the internal heat absorption.

The dimensionless variable can be taken as

$$u = bx^{n} f_{\eta}(\eta), v = -\sqrt{\frac{b \upsilon(n+1)}{2}} x^{\frac{n-1}{2}} \left(f(\eta) + \frac{n-1}{n+1} \eta f_{\eta}(\eta) \right),$$

$$\eta = y_{\sqrt{\frac{b(n+1)}{2\upsilon}}} x^{\frac{n-1}{2}}, \theta(\eta) = \frac{T - T_{\infty}}{T_{w} - T_{\infty}}, \phi(\eta) = \frac{C - C_{\infty}}{C_{w} - C_{\infty}}$$
(8)

Substituting Eq. (8) into Esq. (1) - (4), we obtain the ordinary differential equations as follows:

$$f''' - \left(\frac{2n}{n+1}\right)f'^2 + ff'' - Mf' = 0$$
⁽⁹⁾

$$\theta'' + \Pr\left[f\theta' + Ecf''^{2} + Nb\theta'\phi' + Nt\theta'^{2} - \left(\frac{2}{n+1}\right)\lambda f'\theta\right] + \left(\frac{2}{n+1}\right)B^{*}\theta + \left(\frac{2}{n+1}\right)A^{*}f' = 0$$
(10)

$$\phi'' + Lef\phi' + \frac{Nt}{Nb}\theta'' = 0 \tag{11}$$

© 2017, IJMA. All Rights Reserved

The transformed boundary conditions

$$f(\eta) = 0, f'(\eta) = 1 + \beta f''(\eta), \theta(\eta) = 1, \varphi(\eta) = 1 \text{ at } \eta = 0$$

$$f'(\eta) \to 0, \theta(\eta) \to 0, \varphi(\eta) \to 0 \text{ as } \eta \to \infty.$$
 (12)

where the prime denotes differentiation with respect to η .

$$M = \frac{2\sigma B_0^2}{\rho_f b(n+1)}, \operatorname{Pr} = \frac{\upsilon}{\alpha}, Ec = \frac{u_w^2}{c_p(T_w - T_\infty)}, Nb = \frac{(\rho c)_p D_B(C_w - C_\infty)}{(\rho c)_f \upsilon},$$

$$Le = \frac{\upsilon}{D_B}, Nt = \frac{(\rho c)_p D_T(T_w - T_\infty)}{(\rho c)_f T_\infty \upsilon}, \ \beta = A_1 \sqrt{\frac{b\upsilon(n+1)}{2}} x^{\frac{n-1}{2}}$$
(13)

The special interests and importance of the present problem of nano fluid, in this study, the local skin-friction, Nusselt number and Sherwood number are defined as $\sqrt{}$

$$C_{fx} = \frac{\mu_f}{\rho u_w^2} \left[\frac{\partial u}{\partial y} \right]_{y=0}, \quad Nu_x = \frac{xq_w}{k(T_w - T_\infty)}, \quad Sh_x = \frac{xq_m}{D_B(C_w - C_\infty)}$$
(14)

Where k is the thermal conductivity of the nanofluid and q_w , q_m are the heat and mass fluxes at the surface, given by

$$q_{w} = -\left\lfloor \frac{\partial \mathbf{T}}{\partial y} \right\rfloor_{y=0}, \ q_{m} = -D_{B} \left\lfloor \frac{\partial C}{\partial y} \right\rfloor_{y=0}$$
(15)

Substituting Eq. (6) into Eqs. (14)-(15), we obtain

$$\operatorname{Re}_{x}^{1/2} Cf_{x} = \sqrt{\frac{n+1}{2}} f''(0), \ \operatorname{Re}_{x}^{-1/2} Nu_{x} = -\sqrt{\frac{n+1}{2}} \theta'(0), \ \operatorname{Re}_{x}^{1/2} Sh_{x} = -\sqrt{\frac{n+1}{2}} \phi'(0)$$
(16)

Where $\operatorname{Re}_{x} = u_{w} x / v$ is the local Reynolds number.

METHOD OF SOLUTION

The system of nonlinear ordinary differential equations in Eqs.(9)–(11) with the boundary conditions (12) are solved numerically by means of a finite-difference scheme known as the Keller-box method, the following steps are involved to achieve the Numerical solution.

- Reduce the non-linear higher order ordinary differential equations into a system of first order ordinary differential equations.
- Write the finite differences for the first order equations.
- Linearize the algebraic equations by Newton's method, and write them in matrix-vector form. Solving the linear system by the block tri-diagonal elimination technique.
- In order to solve the above differential equations numerically, we adopt Matlab software which is very efficient in using the well known Keller box method.

For getting accuracy of this method to choose appropriate initial guesses.

$$f(\eta) = \frac{1}{(1+\beta)} (1-e^{-\eta}), \theta(\eta) = e^{-\eta}, \varphi(\eta) = e^{-\eta}$$

The step size $\delta = 0.006$ is used to obtain numerical solution with four decimal place accuracy as criterion of convergence.

RESULT AND DISCUSSION

The aim of this paper is to discuss the effect of various physical parameters such as magnetic parameter (M), velocity slip parameter (β), prandtl number (Pr), viscous dissipation parameter (Ec), Brownian motion parameter (Nb), themoporesis parameter (Nt), Lewis number (Le) and non-uniform heat source/sink parameters (A^*) and (B^*) on velocity, temperature and concentration profiles. The transformed momentum, energy and concentration Eqs. (9) to (11) and boundary conditions (12) were numerically solved by using Keller-Box method. The numerical results were discussed for the various values of the parameters graphically and in tabular form. To validate the present results, comparisons have been made with previous results (Nandeppanavar *et al.* [25]) for local nusselt number $-\theta'(0)$ for various values of A*, B*, λ and Pr in the absence of M, β , Le, Nb, Nt and Ec are presented in table-1 and which are found in good agreement.

Effects of β , Ec, Nb, Nt, Le and M when Pr = 1.0, n = 0.5, $A^* = B^*=0.1$, $\lambda = 2.0$ on skin-friction, local Nusselt and loacal Sherwood numbers are presented in Table 2. It is to found that skin friction coefficient increases for different values of magnetic parameter M, but skin friction coefficient slowly decreases with increasing in β .

| | Values | -	heta'(0) | | | | | | | |
|-----------|--------|-------------|---------------|-----------------|----------|----------|----------|--|--|
| Parameter | | Mahantesh M | . Nandeppanav | Present Results | | | | | |
| | | n = 0.5 | n = 1.0 | n = 1.5 | n = 0.5 | n = 1.0 | n = 1.5 | | |
| λ | 1.0 | 0.994706 | 0.864169 | 0.784960 | 0.994701 | 0.864167 | 0.784953 | | |
| | 2.0 | 1.452543 | 1.237484 | 1.100034 | 1.452538 | 1.237484 | 1.100025 | | |
| | 3.0 | 1.818398 | 1.544861 | 1.365733 | 1.818377 | 1.544858 | 1.365733 | | |
| Pr | 1.0 | 1.452443 | 1.237484 | 1.00034 | 1.452441 | 1.237484 | 1.000025 | | |
| | 2.0 | 2.226426 | 1.927176 | 1.732455 | 2.226422 | 1.927167 | 1.732449 | | |
| | 3.0 | 2.799134 | 2.436357 | 2.199036 | 2.799130 | 2.436321 | 2.199032 | | |
| A^{*} | -0.1 | 1.561825 | 1.354497 | 1.22213 | 1.561825 | 1.354478 | 1.222150 | | |
| | 0.0 | 1.507134 | 1.295990 | 1.161123 | 1.507134 | 1.295989 | 1.161122 | | |
| | 0.1 | 1.452443 | 1.237484 | 1.00034 | 1.452441 | 1.237484 | 1.100025 | | |
| B^{*} | -0.1 | 1.560166 | 1.334991 | 1.188739 | 1.560163 | 1.334991 | 1.188737 | | |
| | 0.0 | 1.508454 | 1.288311 | 1.146251 | 1.508455 | 1.288311 | 1.146250 | | |
| | 0.1 | 1.452443 | 1.237484 | 1.100034 | 1.452441 | 1.237484 | 1.100025 | | |

Table-1: Comparison values of Local Nusselt number $-\theta'(0)$ for several values of the flow parameters.

Table-2: Calculation of -f''(0), $-\theta'(0)$ and $-\phi'(0)$ for various flow parameters when Pr = 1.0, n = 0.5, A* = B*=0.1, $\lambda = 2.0$

| Μ | Ec | Nb | Nt | Le | β | -f''(0) | -	heta'(0) | $-\phi'(0)$ |
|-----|-----|-----|-----|-----|-----|---------|------------|-------------|
| 0.0 | | | | | | 0.7717 | 1.1806 | 0.0414 |
| 0.1 | 0.5 | | | | | 0.8224 | 1.1552 | 0.0428 |
| 0.2 | | 0.1 | 0.1 | 2.0 | 0.1 | 0.8705 | 1.1306 | 0.0449 |
| | 0.0 | | | | | 0.8224 | 1.2764 | -0.0602 |
| | 0.1 | | | | | | 1.2521 | -0.0396 |
| 0.1 | 0.3 | | | | | | 1.2037 | -0.0016 |
| | 0.5 | 0.1 | | | | | 1.1552 | 0.0428 |
| | | 0.3 | | | | | 1.0889 | 0.6130 |
| | | 0.5 | | | | | 1.0266 | 0.7263 |
| | | 0.1 | 0.1 | | | | 1.1552 | 0.0428 |
| | | | 0.3 | | | | 1.1203 | -1.5260 |
| | | | 0.5 | | | | 1.0877 | -2.9918 |
| | | | 0.1 | 2.0 | | | 1.1552 | 0.0428 |
| | | | | 3.0 | | | 1.1463 | 0.3490 |
| | | | | 5.0 | | | 1.1350 | 0.8152 |
| | | | | 2.0 | 0.1 | 0.8224 | 1.1552 | 0.0428 |
| | | | | | 0.5 | 0.5280 | 1.0106 | 0.0162 |
| | | | | | 0.7 | 0.4423 | 0.9490 | 0.0151 |

Fig. 2 shows that the effect of magnetic field (M) on velocity profile. It is observed that an increase in magnetic field decreases the velocity of the fluid. This is due to the fact that as Lorentz force increases the magnetic field generate an opposite force to the flow. This Lorentz force may slow down the velocity of the fluid in the stretching case. As the values of magnetic parameter M increase, the retarding body force enriches and as a result the velocity reduces.

Y. Dharmendar Reddy^{1*}, V. Srinivasa Rao², L. Anand Babu³ / Viscous Dissipation and Partial slip effects on MHD Boundary layer flow of nanofluidand Heat transfer over a nonlinear stretching sheet with non-uniform heat source / IJMA- 8(8), August-2017.



Figure-2: Effect of Magnetic field M on velocity profile



Figure-3: Effect of Magnetic field M on temperature profile



Figure-4: Effect of Magnetic field M on concentration profile

Effect of magnetic parameter (M) on temperature and concentration profiles are presented in figs. 3 and 4. From these figures, we observed that an increase in magnetic parameter enhances both the temperature and concentration profiles of the fluid phase in the nonlinear stretching surface. Physical significance of this behavior is, As Lorentz force is a frictional resistive force opposes the fluid motion and therefore heat produced. According to result, the thermal boundary layer thickness and concentration boundary layer thickness become heavier for stronger magnetic field. © 2017, IJMA. All Rights Reserved 6

Figs.5, 6 and 7 demonstrates the effect of velocity slip parameter (β) on velocity, temperature and concentration profiles. From the figure 5 it is observed that the velocity profile decreases with increasing values of β . As the velocity slip parameter increases, the slip velocity increases and the fluid velocity decreases. The reason for this phenomena is when the slip condition occurs, the velocity of the stretching sheet is not same as the velocity of the flow near the sheet. The effect of velocity slip parameter on the temperature profile and the concentration profile are presented in Figs. 6 and 7. In the presence of a magnetic field and a thermal jump, it is observed that the temperature and concentration profiles increases as the value of the velocity slip parameter β increases.



Figure-5: Effect of velocity slip parameter β on velocity profile



Figure-6: Effect of velocity slip parameter β on temperature profile



Figure-7: Effect of velocity slip parameter β on concentration profile

Figure 8 depicts the influence thermophoresis parameter (Nt) and Brownian motion parameter (Nb) on temperature profile. As the thermophoretic and Brownian motion parameters increases, the movement of nanoparticles from the hot surface to cold surface and ambient fluid is occurred, as result the temperature increases in the boundary layer, this results in the growth of thermal boundary layer thickness.



Figure-8: Effect of Nb and Nt on temperature profile



Figure-9: Effect of Nb on concentration profile



Figure-10: Effect of Nt on concentration profile

Figure 9 illustrates the effect of Brownian motion parameter (Nb) on concentration profile. The nanoparticle concentration profile decreases with the increase in the Brownian motion parameter Nb. Brownian motion attends to warm the boundary layer and simultaneously infuriates particle deposition away from the fluid regime or onto the surface, thereby describing for the reduced concentration magnitudes. For large particles and clearly Brownian motion does maintain a significant enhancing influence on concentration profiles. The converse is the case, for minor particles and Brownian motion is strong and the parameter Nb will have high values. Figure 10 shows the effect of thermophoresis parameter (Nt) on concentration profile. We observed that the concentration profile is increased with increasing values of thermophoresis parameter Nt. This is due to the fact that the thermophoretic force is produced by the temperature gradient and it creates a very high speed flow away from the stretching sheet. Hence the concentration profile $\phi(\eta)$ increases at the surface.



Figure-11: Effect of A* on temperature profile



Figure-12: Effect of B* on temperature profile

Figs. 11 and 12 depict the effect of non-uniform heat source/sink parameter on the temperature profiles of the flow. It is observed from the figures that an increase in the values of A*, B* increases the temperature profiles of the flow. The positive values of non-uniform heat source/sink parameters behave like heat generators. Producing the heat causes to release the heat energy to the flow and hence raises the temperature profiles of the flow. This agrees with the general physical behavior of heat source parameter.



Figure-13: Effect of Eckert number Ec on temperature profile

Fig.13. illustrates the effects of the viscous dissipation parameter (Eckert number) Ec on the temperature. It can be seen that the temperature increases with increasing values of Ec and that the thermal boundary layer thickness also increases. This is due to the fact that heat energy is stored in the liquid due to the frictional heating. The effect of increasing Ec, is to enhance the temperature at any point.



Figure-14: Effect of Lewis number Le on concentration profile

Fig. 14.depicts the influence of the Lewis number on the concentration profile. It is noticed that the nanoparticle volume fraction experiences a strong reduction for larger Le values. The dimensionless Lewis number is defined as the ratio of thermal and mass diffusivity. By increasing the value of Le, the thermal boundary layer thickness is increased whereas the concentration boundary layer thickness is reduced.



Figure-15: Effect of λ on temperature profile

Fig. 15 shows that the effect of the parameter λ on temperature distribution. It can be observed that the direction of heat transfer depends on the magnitude of the parameter λ . From fig. 15 it can be seen that, the increasing values of λ is to decrease the magnitude of temperature in the boundary layer, and hence there is heat transfer from sheet to liquid.



Figure-16: Effect of non-linear stretching sheet parameter (n) on velocity profile



Figure-17: Effect of non-linear stretching sheetparameter (n) on temperature profile

The effect of non-linear stretching sheetparameter (n) is discussed in Fig. 16 & Fig. 17. It is evident that as the nonlinear stretching parameter n increases, velocity profiles are decreases whereas temperature distribution is accelerate.

The variations of quantities of the physical interest from engineering point of view. That is, local skin friction -f''(0) and the local Nusselt number $-\theta'(0)$. Fig. 18 and 19 reveals that for higher values of magnetic parameter M and non-linear stretching parameter n, the Skin friction coefficient and local Nusselt number shows the increasing behavior. This means that fluid motion on the wall of the sheet is increased.



Figure-18: variation of -f''(0) for different values of Magnetic field M and non-linear stretching sheet parameter n.



Figure-19: variation of $-\theta'(0)$ for different values of Magnetic field M and non-linear stretching sheet parameter n.



Figure-20: variation of $-\theta'(0)$ with thermophores is parameter Nt for different values of Brownian motion parameter Nb.

Figure 20 shows the effect of both Brownian motion parameter Nb and thermophoresis parameter Nt on local Nusseltnumber $-\theta'(0)$. It is observed that, as Nt&Nb increase, the heat transfer rate on the surface of a sheet decreases. This indicates that an increment in thermophoresis parameter induces resistance to the diffusion of mass.

© 2017, IJMA. All Rights Reserved

CONCLUSIONS

The problem of MHD boundary layer flow of nanofluids and heat transfer over a nonlinear stretching sheet with viscous dissipation, non-uniform heat source and velocity slip condition has been investigated numerically. Similarity solutions are presented which effects magnetic field, nonlinearly stretching sheet, Brownian motion parameter, thermophoresis parameter, viscous dissipation, velocity slip parameter and Lewis number. The governing partial differential equations were transformed to non-linear ODEs with the help of similarity transformations. The solution of the problem was obtained numerically using Keller box method.

The following conclusions have been drawn from the present study:

- 1. Velocity distribution decreases with increasing the values of Magnetic field M, whereas temperature and concentration profiles are increases.
- 2. The effect of increasing values of velocity slip parameter (β) is to decrease the velocity distribution, but increase the temperature and concentration distributions in flow region.
- 3. An increase in Brownian motion parameter and thermophoresis parameter inceases the temperature distribution.
- 4. Concentration profiles are decreased with increasing of Brownian motion parameter, whereas it increases when the thermophoresis parameter increases.
- 5. The internal heat generation/absorption parameters space dependent (A^*) and temperature dependent (B^*) increases then temperature profiles are also increases.
- 6. It is noted that with increasing values of Eckert number (Ec) the surface temperature increases.
- 7. Concentration profiles are reduced with the larger values of Lewis number.
- 8. The rate of heat transfer increases with the increasing values of non-linear stretching parameter, magnetic parameter. Whereas it decreases with increasing values of Brownian motion parameter and thermophoresis parameter.
- 9. Skin-friction coefficient increases with increasing values of non-linear stretching parameter and magnetic parameter.

REFERENCES

- 1. L. J. Crane, Flow past a stretching plate, Journal of Applied Mathematic and Physics (ZAMP), Vol. 21, Issue 4, pp. 645-647, 1970.
- 2. R. Cortell, Fluid flow and radiative nonlinear heat transfer over a stretching sheet, Journal of King Saud University Science (2014) 26, 161–167.
- 3. K.V. Prasad, K. Vajravelu, P.S. Datti, The effects of variable fluid properties on the hydro-magnetic flow and heat transfer over a non-linearly stretching sheet International Journal of Thermal Sciences 49 (2010) 603–610.
- 4. M. Subhas Abel and Mahantesh M. Nandeppanavar, Heat transfer in MHD viscoelastic boundary layer flow over a stretching sheet with non-uniform heat source/sink, Commun Nonlinear Sci Numer Simulat 14 (2009) 2120–2131.
- 5. Mahantesh M. Nandeppanavar, K. Vajravelu, M. Subhas Abel, M.N. Siddalingappa, MHD flow and heat transfer over a stretching surface with variable thermal conductivity and partial slip, Meccanica (2013) 48:1451–1464.
- 6. Asterios Pantokratoras, Study of MHD boundary layer flow over a heated stretching sheet with variable viscosity: A numerical reinvestigation, International Journal of Heat and Mass Transfer, Volume 51, Issues 1–2, January 2008, Pages 104-110.
- Choi, S. U. S., (1995). "En hancing thermal conductivity of fluids with nanoparticles, ASME Int. Mech. Eng. Congress. San Francisco, USA, ASME, FED, 231/MD., 66: 99-105.
- 8. W.A. Khan, I. Pop, Boundary-layer flow of a nanofluid past a stretching sheet, International Journal of Heat and Mass Transfer 53 (2010) 2477–2483.
- F.Mabood ,W.A.Khan , A.I.M.Ismail ,MHD boundarylayer flow and heat transfer of nanofluids over a nonlinear stretching sheet: Anumericalstudy, Journal of Magnetism and Magnetic Materials 374(2015) 569–576.
- A. Malvandi1,F. Hedayati2 and M. R. H. Nobari, An Analytical Study on Boundary Layer Flow and Heat Transfer of Nanofluid Induced by a Non-Linearly Stretching Sheet *Journal of Applied Fluid Mechanics*, Vol. 7, No. 2, pp. 375-384, 2014.
- 11. Mohsen Sheikholeslami, Shirley Abelman, Davood Domiri Ganji, Numerical simulation of MHD nanofluid flow and heat transfer considering viscous dissipation, International Journal of Heat and Mass Transfer 79 (2014) 212–222.
- 12. P.K. Kameswaran, M. Narayana, P.Sibanda and P.V.S.N.Murthy, Hydromagnetic nanofluid flow due to a stretching or shrinking sheet with viscous dissipation and chemical reaction effects, International Journal of Heat and Mass Transfer, Volume 55, Issues 25–26, pp. 7587-7595 (2012).

- 13. Dulal Paland Gopinath Mandal, Mixed convection-radiation on stagnation-point flow of nanofluids over a stretching/shrinking sheet in a porous medium with heat generation and viscous dissipation, Journal of Petroleum Science and Engineering, Volume 126, February 2015, pp. 16-25.
- 14. Rizwan Ul Haq, Sohail Nadeem, Zafar Hayat Khan and Noreen Sher Akbar, Thermal radiation and slip effects on MHD stagnation point flow of nanofluid over a stretching sheet, Physica E 65 (2015) 17–23
- 15. Rana P., Bhargava R., (2011). "Numerical study of heat transfer enhancement in mixed convection flow along a vertical plate with heat source/sink utilizing nanofluids", Commun. Nonlinear Sci. Numer.Simul., 16: 4318-4334.
- Nandy S. K., Mahapatra T. R., (2013). "Effects of slip and heat generation/absorption on MHD stagnation point flow nanofluid past a stretching/shrinking surface with convective boundary conditions", Int. J. Heat Mass Transf., 64, 1091-1100.
- A. Alsaedi, M. Awais and T. Hayat, Effects of heat generation/absorption on stagnation point flow of nanofluid over a surface with convective boundary conditions, Commun Nonlinear Sci Numer Simulat 17 (2012) 4210–4223.
- 18. Aminreza Noghrehabadi, Rashid Pourrajab and Mohammad Ghalambaz, Effect of partial slip boundary condition on the flow and heat transfer of nanofluids past stretching sheet prescribed constant wall temperature, International Journal of Thermal Sciences 54 (2012) 253-261.
- 19. Swati Mukhopadhyay and Iswar Chandra Mandal, Magnetohydrodynamic (MHD) mixed convection slip flow and heat transfer over a vertical porous plate, Engineering Science and Technology, an International Journal, Volume 18, Issue 1, March 2015, Pages 98-105.
- 20. M. Mustafa, S. Hina , T. Hayat , A. Alsaedi, Slip Effects on the PeristalticMotion of Nanofluid in a Channel With Wall Properties, Journal of Heat Transfer, Vol. 135(4), 041701(2013).
- 21. Krishnendu Bhattacharyya, Swati Mukhopadhyay and G.C.Layek, Slip effects on boundary layer stagnationpoint flow and heat transfer towards a shrinking sheet, International Journal of Heat and Mass Transfer, Volume 54, Issues 1–3, 15 January 2011, pp. 308-313.
- 22. Naramgari Sandeep, Chalavadi Sulochana and Banglore Rushi Kumar, Flow and Heat Transfer in MHD Dusty Nanofluid Past a Stretching/Shrinking Surface with Non-Uniform Heat Source/Sink, Walailak J Sci & Tech 2017; 14(2): 117-140.
- 23. Dulal Pal and Gopinath Mandal, Thermal radiation and MHD effects on boundary layer flow of micropolar nanofluid past a stretching sheet with non-uniform heat source/sink, International Journal of Mechanical Sciences, Volume 126, June 2017, Pages 308–318.
- 24. Tasawar Hayat, Sajid Qayyum, Ahmed Alsaedi and Anum Shafiq, Inclined magnetic field and heat source/sink aspects in flow of nanofluidwith nonlinear thermal radiation, International Journal of Heat and Mass Transfer 103 (2016) 99–107.
- 25. Mahantesh M. Nandeppanavar, K. Vajravelu, M. Subhas Abel and Chiu-On Ng, Heat transfer over a nonlinearly stretching sheet with non-uniform heat source and variable wall temperature, International Journal of Heat and Mass Transfer 54 (2011) 4960–4965.

Source of support: Nil, Conflict of interest: None Declared.

[Copy right © 2017. This is an Open Access article distributed under the terms of the International Journal of Mathematical Archive (IJMA), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.]